



US007681672B2

(12) **United States Patent**
Spalletta

(10) **Patent No.:** **US 7,681,672 B2**
(45) **Date of Patent:** **Mar. 23, 2010**

(54) **CRYOGENIC PULSEJET AND METHOD OF USE**

(75) Inventor: **Robert A. Spalletta**, Scranton, PA (US)

(73) Assignee: **The University of Scranton**, Scranton, PA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 257 days.

(21) Appl. No.: **11/886,373**

(22) PCT Filed: **Mar. 23, 2006**

(86) PCT No.: **PCT/US2006/011093**

§ 371 (c)(1),
(2), (4) Date: **Sep. 15, 2007**

(87) PCT Pub. No.: **WO2006/105014**

PCT Pub. Date: **Oct. 5, 2006**

(65) **Prior Publication Data**

US 2009/0050367 A1 Feb. 26, 2009

Related U.S. Application Data

(60) Provisional application No. 60/666,970, filed on Mar. 31, 2005.

(51) **Int. Cl.**
E21B 7/18 (2006.01)
E21B 43/114 (2006.01)
C09K 8/02 (2006.01)
E21B 36/00 (2006.01)
E21B 7/00 (2006.01)

(52) **U.S. Cl.** **175/424; 175/17**

(58) **Field of Classification Search** **175/424, 175/17**

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,621,022 A * 12/1952 Bardill 175/17
3,424,254 A * 1/1969 Huff 175/17
3,482,640 A * 12/1969 Browning 175/14
3,650,337 A * 3/1972 Andrews et al. 175/17
4,516,878 A * 5/1985 Rebhan 405/130

* cited by examiner

Primary Examiner—Jennifer H Gay


Assistant Examiner—Cathleen R Hutchins

(74) *Attorney, Agent, or Firm*—Charles L. Riddle; Riddle Patent Law

(57) **ABSTRACT**

A cryogenic system is described for boring a small-diameter hole through various materials including rock, soil and stone. It employs a valveless technique in a borehead [3000] where cryogenic fluid [7] fills at least one pulsejet [3100] which has proximal [3001] and distal [3003] ends. The cryogenic fluid [7] is frozen into a plug [8] near the distal end [3003], acting as a valve. Cryogenic fluid [7] just distal to the frozen plug [8] is rapidly heated by thermal units [3510, 3530] causing it to become a rapidly-expanding gas bubble. The rapidly-expanding gas bubble forces any liquid [7] distal to the expanding gas out of the distal end [3003] of each pulsejet [3100] causing it to impact the material [1]. Rapidly repeating this process causes the system to bore a hole through the material [1].

19 Claims, 5 Drawing Sheets






Fig. 1




FIG. 2c




FIG. 2b




FIG. 2a




FIG. 2f

FIG. 2e

FIG. 2d




FIG. 3




FIG. 4

CRYOGENIC PULSEJET AND METHOD OF USE

CROSS REFERENCE TO RELATED APPLICATIONS

The present application claims priority from U.S. Provisional Patent Application "The Archimedes Javelin" Ser. No. 60/666,970 filed Mar. 31, 2005 by Wojciech Andrew Berger, Robert A. Spalletta, Jerry A. Carter, Marian Mazurkiewicz, Richard M. Pell, Christopher Davey. The present Patent Application is also related to U.S. patent application Ser. No. 11/886,374 (U.S. Pat. No. 7,584,807) entitled "System for Rapidly Boring Through Materials" and U.S. patent application Ser. No. 11/886,372 "Multiple Pulsejet Boring Device" both filed on Sep. 15, 2007 by Wojciech Andrew Berger, Robert A. Spalletta, Jerry A. Carter, Richard M. Pell, Marian Mazurkiewicz. All above applications are hereby incorporated by reference as if set forth in its entirety herein.

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates to a valveless cryogenic system for boring through materials.

2. Discussion of Related Art

There currently are prior art boring devices and other machinery which are designed to drill through materials, such as rock and earth. Many of these employ mechanical rotary drills. Which require strong structures to anchor the drill and counter the rotational forces.

Other drills exist which employ forcing a high pressure liquid at the material to bore through it. These require a great deal of pressure to be passed to the cutting end of the drill.

Since many of the materials being bored are brittle, prior art cryogenic drills have been used. These use high pressure (but not as high as the liquid cutting drills) to force cryogenic liquid at a brittle object, freezing it and impacting it with the cryogenic liquid. The frozen material is more brittle and fractures when impacted by the cryogenic liquid.

Since these apply high pressure to the cutting tip, which may be some distance away, it has structural requirements not only to contain the pressure and pass it to the tip, but also to keep the cryogen cool. These tend to make the drill bulky and hard to manage.

In addition, these require a valved system to intermittently allow and stop the fluid to create a stream of pulsed liquid slugs which impact the target.

These valves are acting under extreme conditions and tend to freeze and fail.

Currently, there is a need for a low pressure drilling device which is more effective than prior art devices.

SUMMARY OF THE INVENTION

One embodiment of the present invention is a cryogenic rapid boring system for rapidly boring a hole in a material (1) comprising:

- a) A borehead (3000) having at least one pulsejet (3100) with a proximal end (3001) and a distal end (3003) located adjacent said material (1) intended to be bored;
- b) A cryogen supply unit (1010) for providing a cryogenic liquid (7) to fill the pulsejet (3100);
- c) The pulsejet (3100) having an expansion section (3120) located adjacent to the distal end (3003);
- d) The tube having a freeze section (3110) located just proximal to the expansion section (3120);

e) At least one thermal unit (3410) capable of freezing cryogenic liquid (7) into a plug (8) and capable of melting frozen plug (8) located adjacent to the freeze section (3110);

f) At least one thermal unit (3510) capable of vaporizing cryogenic liquid (7) into a gas, and capable of cooling the expansion section (3120);

g) A controller (1020) coupled to the cryogen supply unit (1010), the thermal units (3410, 3430, 3510, 3530), operating to activate:

i. the cryogen supply unit (1010) to fill the pulsejet (3100) with cryogenic liquid (7);

ii. thermal units (3410, 3430) to freeze a plug (8) at the freeze section (3110);

iii. thermal units (3510, 3530) to rapidly vaporize cryogenic liquid (7), into a gas just distal to the frozen plug (8) thereby causing it to force cryogenic liquid (7) distal to the gas, out of the distal end (3003) of pulsejet (3100) at a high velocity impacting said material (1) thereby 'firing' the pulsejet (3100).

The present invention may also be embodied as a method of boring through solid material (1) with a cryogenic liquid (7) comprising the steps of:

a. providing a borehead (3000) having at least one pulsejet (3100) capable of holding a liquid, having a distal end (3003) and an opposite proximal end, the distal end being positioned near, and pointing toward said material;

b. providing cryogenic liquid (7) to the proximal end of the pulsejet (3100);

c. freezing the cryogenic liquid (7) near the distal end of the pulsejet (3100) into a plug (8) at a location such that there is cryogenic liquid (7) distal to the plug (8);

d. rapidly heating the cryogenic liquid (7) distal to the plug (8) causing it to be converted into rapidly-expanding gas (9) rapidly forcing the cryogenic liquid (7) distal to the gas (8) out of the distal end of the pulsejet (3100) as a slug (10) which impacts said material (1);

e. repeating steps "b"- "d" to cause multiple slugs (10) to be forced out of the pulsejet (3100) thereby boring a hole through said material (1).

OBJECTS OF THE INVENTION

It is an object of the present invention to provide a system which bores through materials more efficiently than the prior art devices.

It is another object of the present invention to provide a simpler system for boring through materials than the prior art devices.

It is another object of the present invention to provide a more reliable system for boring through materials than the prior art devices.

It is another object of the present invention to provide a valveless cryogenic system for boring through materials.

BRIEF DESCRIPTION OF THE DRAWINGS

The advantages of the instant disclosure will become more apparent when read with the specification and the drawings, wherein:

FIG. 1 is a perspective view of a cryogenic boring system according to one embodiment of the present invention.

FIGS. 2a-2f are enlarged views of a portion of the cryogenic boring device of FIG. 1, showing the operation of the pulsejets.

FIG. 3 is a flowchart illustrating the functioning of the present invention.

FIG. 4 shows an embodiment of the present invention employing multiple cryogenic pulsejets in a single borehead.

DETAILED DESCRIPTION OF THE INVENTION

One embodiment of the present invention is shown in perspective view in FIG. 1. A number of ground units **100**, **4000**, **5000** are delivered to the ground. Unit **100** is positioned just above a target **1** which may be an underground void or object. Ground unit **100** may be delivered there by a number of different conventional known methods including an air-drop for inaccessible locations.

Ground unit **100** employs a platform subsystem **1000** having retention and orientation devices **1500** which secure ground unit **100** to the ground and tilts platform **1000** to an optimum orientation for boring to target **1**. Platform subsystem **1000** is designed to hold, store and carry all the equipment during deployment, initiate boring of an access hole, hold materials to be used in a fuel reservoir, stabilize ground unit **100** for boring, and communicate with other units.

A boring subsystem **3000** bores down through the ground toward target **1**, creating an access hole **5**. Boring subsystem **3000** is designed to force the excavated materials out of the access hole **5** and to the surface.

Boring subsystem **3000** is connected to platform subsystem **1000** by an umbilical subsystem **2000**.

Umbilical subsystem **2000** connects the Platform **1000** and Boring **3000** subsystems. It acts to pass materials, electricity, and control signals between platform **1000** and boring **3000** subsystems.

Umbilical subsystem **2000** also employs mechanical actuators to absorb much of the forces produced during boring, as well as for steering and advancing umbilical subsystem **2000** and boring **3000** subsystems deeper into the access hole **5**.

The boring subsystem **3000** employs pulsejets shown in greater detail in FIGS. 2a-2f.

FIGS. 2a-2f are a time sequence of enlarged views of a pulsejet **3100** of the cryogenic borehead (**3000** of FIG. 1), showing the operation of the pulsejet **3100**.

In FIG. 2a, a pulsejet **3100** is shown in an enlarged view. A cryogenic fluid **7** passes through umbilical **2000** to pulsejet **3100**. Pulsejet **3100** employs a freezing section **3110** near the distal end of pulsejet **3100**. Just distal to the freezing section **3110** is an expansion section **3120**. Just distal to the expansion section is an exit section **3300**.

In FIG. 2a, cryogenic fluid **7** has passed down umbilical **2000** and has filled freeze section **3110**, expansion section **3120** and exit section **3300**. Adjacent to freeze section **3110** is at least one thermal unit **3410**, **3430**. In FIG. 2a both thermal units **3410**, **3430** are inactive. Adjacent to expansion section **3120** is at least one thermal unit **3510**, **3530**. In FIG. 2a both thermal units **3510**, **3530** are inactive.

FIG. 2b shows the system at some time after that of FIG. 2a, thermal units **3410**, **3430** are activated to cause cryogenic fluid **7** in freeze section **3110** to solidify. Preferably, freeze section **3110** is narrower than the remainder of the system allowing quick freezing. At this time thermal units **3510**, **3530** are inactive.

In FIG. 2c, thermal units **3510**, **3530** are activated to provide heat to the cryogenic fluid **7** in expansion region **3120**. Fluid **7** rapidly changes into a gas producing a rapidly-expanding gas bubble **9** pushing fluid **7** in exit section **3300** out as a liquid slug **10**.

An efficient method of supplying electric energy to thermal units **3410**, **3430** first, then to thermal units **3510**, **3530** is to use the Peltier effect

In the Peltier effect, an electric current of magnitude J across the junction of two different conductors A and R with Peltier coefficients Π_A and Π_B produces heat at the rate $\dot{W} - (\Pi_A - \Pi_B) \cdot J$

The sign of \dot{W} can be positive as well as negative. A negative sign means cooling of the junction. Contrary to Joule heating, the Peltier effect is reversible and depends on the direction of the current. In this effect, thermal units **3410**, **3510** are coupled. Thermal units **3430** and **3530** are also coupled. Energy is first provided to thermal units **3410**, **3430**, then by the Peltier effect, the energy is then passed through thermal units **3510** from **3410**; and through thermal unit **3530** from thermal unit **3430**.

In FIG. 2d thermal units **3510**, **3530** have stopped providing heat to fluid **7**. It can be seen here that expansion section **3120** and exit section **3300** are filled with the gas. The liquid slug **10** has been expelled from the exit section at a high velocity. Slug **10** is typically directed to the material which is intended to be bored. Slug **10** freezes and shatters the frozen material, thereby boring through the material.

In FIG. 2e thermal units **3410**, **3430** heat frozen plug **8**, melting it. At the same time, thermal units **3510**, **3530** cool expansion section **3120**, getting it ready to receive more cryogenic fluid **7**.

In FIG. 2f, fluid **7** fills freeze section **3110**, expansion section **3120** and exit section **3300**, putting the system in the state it was in as shown in FIG. 2a. The cycle may now be repeated.

By controlling when thermal units **3410** and **3430** freeze the liquid **7**, one can adjust the amount of liquid distal to the plug **8**. This thereby adjusts the size of the slug **10**.

By controlling how much energy is provided to thermal units **3510** and **3530**, one may adjust the intensity in which the pulsejet **3100** is 'fired'.

The present invention may also be viewed as a novel method of boring through a material.

FIG. 3 is a flowchart illustrating the functioning of the present invention. This invention is a method of drilling through solid materials employing pumping a cryogenic fluid through a pipe into the target material. The process begins at step **301**.

In step **303** a tube extending in a proximal direction and a distal direction is filled with cryogenic fluid.

In step **305**, at a location within the material, a refrigeration section freezes the cryogen in the pipe into a solid "plug".

The cryogenic liquid near the distal end of the tube is frozen into a plug by applying current to freezing coils. This plug is positioned such that there is cryogenic liquid distal to the plug in the tube. The plug at least partially blocks the tube.

In step **307**, the cryogenic liquid distal to the plug is heated, causing a rapidly-expanding gas bubble to form. The rapidly-expanding gas bubble pushes the cryogenic liquid distal to the bubble as a slug out of the end of the distal end of the tube at a high velocity. The frozen cryogen is used as a 'backstop' to bounce against causing the force to cause the liquid to pass outward through the distal end of the tube against the material to be bored.

In step **309**, the plug is rapidly heated to melt it allowing cryogenic fluid again to fill the tube.

In step **311** it is determined if the boring has been completed. If boring has been completed ("yes"), then the process stops at step **313**.

5

If not (“no”), then steps **303** through **311** are repeated. Repeating the sequence causes a plurality of slugs to be rapidly forced out of the tube. The repeated slug impacts destroy and cut through the target material, thereby boring a hole through the material.

The tip may also employ small reverse nozzles which point away from the material to be bored. Some of the escaping gases fire through these reverse nozzles propelling the tip further into the material to be bored.

FIG. **4** shows an embodiment of the present invention employing multiple cryogenic pulsejets in a single borehead. The distal ends of several pulsejets **3101**, **3103**, **3105**, **3107** and **3109** are shown. These pulsejets may be fired in different sequences and intensities to simulate rotary boring and also cause steering.

In one embodiment, slugs **10** are fired in sequence to create the effects of rotary boring and maximize boring efficiency. Here, pulsejets **3101**, **3103**, **3105**, **3107** and **3109** around the periphery of the borehead **3000** are fired in this order creating slugs **10**, shown at various distances from the pulsejets. A controller (**1020** of FIGS. **2a-2f**) activates thermal units (**3510**, **3530** of FIGS. **2a-2f**) at the proper times to create the sequence as shown. This simulates the effect of a rotary drilling in the direction by the arrows marked “A”.

Steering is more fully discussed in “Steerable Boring Device” incorporated by reference in the Cross Reference to Related applications above.

In another embodiment of the present invention, the boring subsystem may be used above ground to cut or shape materials. It works best with materials which become brittle when cooled.

The present invention provides a cryogenic pulse jet source which cuts through hardened materials much more quickly than a steady flow cryogenic jet.

The present invention provides a cryogenic pulse jet that does not require valves which tend to freeze and malfunction. This results in a more reliable system.

The present invention does not require the use of high pressure liquids as do other prior art devices, therefore resulting in a simpler, less bulky system.

The present invention employs the ambient energy of the ground as a heat source to provide a temperature differential used to fracture hard materials in the ground.

Since other modifications and changes varied to fit particular operating requirements and environments will be apparent to those skilled in the art, the invention is not considered limited to the example chosen for the purposes of disclosure, and covers all changes and modifications which do not constitute departures from the true spirit and scope of this invention.

What is claimed is:

1. A cryogenic rapid boring system for rapidly boring a hole in a material comprising:

- a) a borehead having at least one pulsejet with a proximal end and a distal end located adjacent to said material intended to be bored;
- b) a cryogen supply unit for providing a cryogenic liquid to fill the pulsejet;
- c) a pulsejet having an expansion section located adjacent to the distal end;
- d) a tube having a freeze section located just proximal to the expansion section;
- e) at least one thermal unit capable of freezing cryogenic liquid into a plug and capable of melting the frozen plug located adjacent to the freeze section;

6

f) at least one thermal unit capable of vaporizing the cryogenic liquid into a gas, and capable of cooling the expansion section;

g) a controller coupled to the cryogen supply unit, the thermal units, and operating to activate:

- i. the cryogen supply unit to fill the pulsejet with the cryogenic liquid;
- ii. thermal units to freeze the plug at the freeze section;
- iii. thermal units to rapidly vaporize the cryogenic liquid, into the gas just distal to the frozen plug thereby causing the gas to force cryogenic liquid distal to the gas out of the distal end of pulsejet at a high velocity impacting said material thereby firing the pulsejet;
- iv. the thermal units to melt the frozen plug; and
- v. the thermal units to cool the expansion section.

2. The cryogenic rapid boring system of claim **1**, wherein there are multiple pulsejets in the borehead.

3. The cryogenic rapid boring system of claim **1**, wherein the thermal units are electrically coupled and use the Peltier effect to heat and cool the pulsejet.

4. The cryogenic rapid boring system of claim **1**, wherein there are a plurality of the thermal units in the freeze section operating to rapidly freeze the cryogenic liquid into the plug and operating to rapidly melt the plug when activated.

5. The cryogenic rapid boring system of claim **1**, wherein there are a plurality of the thermal units in the expansion section operating to rapidly vaporize the cryogenic liquid into the gas and operating to rapidly cool the expansion section when activated.

6. The cryogenic rapid boring system of claim **2**, wherein the controller is adapted to operate to fire the pulsejets in a predetermined sequence to optimize boring.

7. The cryogenic rapid boring system of claim **2**, wherein the controller is adapted to operate to fire the pulsejets in a predetermined sequence to simulate rotary boring.

8. The cryogenic rapid boring system of claim **1**, wherein the controller is adapted to operate to adjust the intensity of the slug fired from the system.

9. The cryogenic rapid boring system of claim **1**, wherein the controller is adapted to adjust the size of the slug fired from the system.

10. A method of boring through solid material with a cryogenic liquid comprising the steps of:

- a. providing a borehead having at least one pulsejet capable of holding a liquid, having a distal end and an opposite proximal end, the distal end being positioned near, and pointing toward said material;
- b. providing cryogenic liquid to the proximal end of the pulsejet;
- c. freezing the cryogenic liquid near the distal end of the pulsejet into a plug at a location such that there is cryogenic liquid distal to the plug;
- d. rapidly heating the cryogenic liquid distal to the plug causing it the cryogenic liquid to be converted into rapidly-expanding gas rapidly forcing the cryogenic liquid distal to the gas out of the distal end of the pulsejet as a slug which impacts said material;
- e. repeating steps “b”-“d” to cause multiple slugs to be forced out of the pulsejet thereby boring a hole through said material.

11. The method of claim **10** wherein there are a plurality of the pulsejets in the borehead.

12. The method of claim **11** wherein the pulsejets are fired in sequence to simulate rotary drilling.

13. The method of claim **10** wherein thermal units are electrically coupled operating under the Peltier effect to heat and cool the pulsejet.

7

14. The method of claim 10 wherein a plurality of thermal units are employed in a freeze section operating to rapidly freeze the cryogenic liquid into the plug and operating to rapidly melt the plug.

15. The method of claim 10 wherein a plurality of thermal units are employed in an expansion section operating to rapidly vaporize the cryogenic liquid into the gas and operating to rapidly cool the expansion section when activated.

16. The method of claim 10 wherein a plurality of pulsejets are operated in a predetermined sequence to optimize boring.

17. The method of claim 10 wherein a plurality of pulsejets are operated in a predetermined sequence to simulate rotary boring.

8

18. The method of claim 10 wherein the step of rapidly heating comprises the step of:

applying a predetermined amount of power to thermal units so as to produce a predetermined firing intensity of the slug from the pulsejet.

19. The method of claim 10 wherein the step of freezing comprises the step of:

activating thermal units at a predetermined time so as to adjust the size of the slug created and fired from the pulsejet.

* * * * *